

05/13/99

Please type a plus sign (+) inside this box → ☐

PTO/SB/05 (2/98)
Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL (Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))	Attorney Docket No.	448563/163
	First Inventor or Application Identifier	Minoru Usui
	Title	INK CARTRIDGE FOR INK-JET PRINTING APPARATUS
	Express Mail Label No.	EE696179675US

APPLICATION ELEMENTS See MPEP chapter 600 concerning utility patent application contents.	ADDRESS TO: Assistant Commissioner for Patents Box Patent Application Washington, DC 20231
---	---

1. ☒ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)

2. ☒ Specification [Total Pages 38] 1
(preferred arrangement set forth below)
- Descriptive title of the Invention
- Cross References to Related Applications
- Statement Regarding Fed sponsored R & D
- Reference to Microfiche Appendix
- Background of the Invention
- Brief Summary of the Invention
- Brief Description of the Drawings (if filed)
- Detailed Description
- Claim(s)
- Abstract of the Disclosure

3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 28] 1

4. Oath or Declaration [Total Pages 10] 1
a. ☐ Newly executed (original or copy)
b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 17 completed)
[Note Box 5 below]
i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

5. ☐ Incorporation By Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered to be part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

6. ☐ Microfiche Computer Program (Appendix)

7. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
a. ☐ Computer Readable Copy
b. ☐ Paper Copy (identical to computer copy)
c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☐ Assignment Papers (cover sheet & document(s))

9. ☐ 37 C.F.R. § 3.73(b) Statement (when there is an assignee) ☐ Power of Attorney

10. ☐ English Translation Document (if applicable)

11. ☒ Information Disclosure Statement (IDS)/PTO-1449 ☒ Copies of IDS Citations

12. ☐ Preliminary Amendment

13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
* Small Entity Statement(s) ☐ Statement filed in prior application, Status still proper and desired (PTO/SB/09-12)

14. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)

15. ☐ Other:

* NOTE FOR ITEMS 1 & 14: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

17. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:
☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: _____
Prior application information: Examiner _____ Group / Art Unit: _____

18. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label [] or ☐ Correspondence address below
(Insert Customer No. or Attach bar code label here)

Name: Stroock & Stroock & Lavan LLP

Address: 180 Maiden Lane

City: New York State: N.Y. Zip Code: 10038

Country: Telephone: (212) 806-5400 Fax: (212) 806-6006

Name (Print/Type)	Howard M. Gitten	Registration No. (Attorney/Agent)	32,138
Signature		Date	5/13/99

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

APPLICATION OF
MINORU USUI
SATOSHI SHINADA
TAKAHIRO NAKA
HISASHI MIYAZAWA
TAKEO SEINO
HISASHII KOIKE
TAKAO KOBAYASHI
MASAHIRO KANAI
YASUKO HIRANO
YASUSHI AKATSUKA
TAKAYUKI IJIMA
NORIAKI OKAZAWA
HITOSHI MATSUMOTO
and
YASUHIRO OGURA

FOR LETTERS PATENT OF THE UNITED STATES

FOR IMPROVEMENTS IN

INK CARTRIDGE FOR INK-JET
PRINTING APPARATUS

Lawrence Rosenthal
Registration No. 24,377
Attorney for Applicant
STROOCK & STROOCK & LAVAN LLP
180 Maiden Lane
New York, New York 10038
(212) 806-5400

448563/163

Express Mail mailing label No.
Number EE 696 179675 US
Date of Deposit 5/13/99
I hereby certify that this paper or fee is being de-
posited with the United States Postal Service "Express
Mail Post Office to Addressee" service under 37 CFR
1.10 on the date indicated above and is addressed to
the Assistant Commissioner for Patents,
Washington, D.C. 20231.
Name Li-Hsi Jakob
Signature [Signature]

INK CARTRIDGE FOR INK-JET PRINTING APPARATUS

BACKGROUND OF THE INVENTION

Field of the Invention:

The present invention relates to an ink cartridge detachably mounted on a carriage, and in particular to a cartridge for an ink jet printer.

Related Art:

A conventional ink cartridge mounted on a carriage for an ink jet printer typically includes a container having on one wall thereof an ink supply port where an ink supply needle of a printing apparatus is inserted, and an opening on the other wall thereof which is sealed by a lid as disclosed, for example, in Japanese published unexamined patent application No. Hei. 8-132635. The container accommodates therein a porous body impregnated with ink. The porous body is formed of polymeric resin.

For an ink cartridge installed in a printing apparatus wherein color printing is enabled, a single container is divided into plural chambers by one or more partitions. A porous body impregnated with ink is housed in each chamber while an ink supply port is formed in each chamber. A film for sealing a respective opening of each ink supply port is provided when mounting the ink cartridge provided with plural ink supply ports as described above on a carriage on which ink supply needles of the same number are secured, the needles must each pierce a respective film. Therefore, a large urging force is required for a user when mounting the cartridge. Therefore, there has been proposed a printing device designed to have a pivotable lever, one end of which is attached to the carriage, so that the ink cartridge can readily be mounted on the carriage by simply operating the lever.

However, although a cartridge can be mounted with small urging force, misposition of the cartridge with respect to the carriage may occur by rough insertion. Further, as the bottom of the cartridge is pushed with large force in a state in which the bottom comes into engagement with ink supply needles in a case where the cartridge is mounted in a wrong direction, there arises a problem that the ink supply needles are broken.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the invention to provide an improved cartridge for an ink jet printer.

An ink cartridge includes an ink container for accommodating ink therein. An ink supply port is formed on the ink container for receiving an ink supply needle, the ink supply needle communicating with a print head attached to the carriage. One or more recessed parts are formed in the container for receiving a projection protruding from the carriage of the printing apparatus; the recessed part being formed in a position to face the projection. The projection is formed in the vicinity of the ink supply needle in a state in which when the ink cartridge is installed in a regular, proper direction the projection of the carriage inserts into the recessed part of the ink cartridge. The height of the protrusion is designed to be higher than that of the ink supply needle.

When the ink cartridge is properly mounted on the carriage of the printing apparatus, the projection on the carriage first fits into the recessed part of the cartridge, and then the ink supply needle inserts into the ink supply port of the cartridge by further urging the ink cartridge against the carriage. On the other hand, if the ink cartridge is mounted in an improper

direction, the projection first comes into abutment against the bottom of the cartridge, and the cartridge cannot be mounted on the carriage.

Another object of the present invention is to provide an ink cartridge capable of fitting onto one or more ink supply needles communicating with a print head only when the cartridge is in a proper position with respect to an ink-jet printing apparatus.

A further object of the present invention is to provide an ink cartridge capable of preventing the ink supply needle of a printing apparatus from being broken due to improper installation of the ink cartridge on the ink-jet printing apparatus.

Still other objects and advantages of the invention will in part be obvious and will in part be apparent from the specification.

The invention accordingly comprises the features of construction, combination of elements, and arrangement of parts which will be exemplified in the construction hereinafter set forth, and the scope of the invention will be indicated in the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

For a fuller understanding of the invention, reference is had to the following description taken in connection with the accompanying drawings (s), in which:

Fig. 1 is a schematic perspective view showing an ink-jet type printing apparatus;

Fig. 2 is a perspective enlarged view of a carriage and a cartridge holder mounting an ink cartridge thereon according to the present invention;

Fig. 3 is a top plan view of the carriage and the cartridge holder shown in Fig. 2;

Fig. 4 is a perspective view showing the structure of the rear side of the above cartridge holder shown in Figs. 2 and 3;

Fig. 5(a) is a top plan view showing the cartridge holder in a state where a print head and a sealing plate are detached therefrom;

Fig. 5(b) is a top plan view showing the sealing plate;

Figs. 6(a) to 6(c) are perspective views of a color ink cartridge according to one embodiment of the present invention respectively showing the structure of the upper surface of a lid in a state in which a film is detached, the structure on the side of an ink supply port and the structure of the upper surface of the lid in a state in which the film is present;

Figs. 7(a) to 7(c) are perspective views of a black ink cartridge according to another embodiment of the present invention respectively showing the structure of the upper surface of a lid in a state in which a film is detached, the structure on the side of an ink supply port, and the structure of the upper surface of the lid in a state in which the film is present;

Fig. 8 is a side sectional view showing the structure of the ink cartridge lid;

Figs. 9(a) and 9(b) are side sectional views demonstrating installation of the ink cartridge in the cartridge holder;

Figs. 10(a) and 10(b) are side sectional views of an improperly mounted ink cartridge within the cartridge holder respectively showing a state in which the ink cartridge is installed with the film of the ink cartridge not peeled off and a state in which the ink cartridge is installed in a reverse direction;

Figs. 11(a) to 11(c) show other methods of sticking a sealing film for sealing the lid according to the present invention;

Fig. 12 is a sectional view of a cartridge lid showing another embodiment of a communicating passage formed therein according to the present invention;

Figs. 13 is a side sectional view showing another embodiment of a mechanism for installing an ink cartridge;

Figs. 14(a) and 14(b) are respectively a perspective view and a top plan view showing another embodiment of the ink cartridge;

Figs. 15(a) and 15(b) are respectively a perspective view and a bottom plan view showing a further embodiment of the ink cartridge;

Figs. 16(a) and 16(b) are respectively a top view plan showing a structure in which recessed parts are arranged and a top view plan showing the structure of a convex part in the vicinity of an ink supply needle and corresponding to the recessed parts respectively in accordance with another embodiment of the color ink cartridge according to the present invention;

Figs. 17(a) and 17(b) are respectively a top view plan showing structure in which recessed parts are arranged and a top plan view showing the structure of a convex part in the vicinity of an ink supply needle and corresponding to the recessed parts respectively in still another embodiment of the color ink cartridge according to the present invention;

Figs. 18(a) and 18(b), Figs. 19(a) and 19(b), Figs. 20(a) and 20(b), and Figs. 21(a) and 21(b) are respectively top plan view showing structure in which recessed parts are arranged and top plan view showing the structure of a convex part in the vicinity of an ink supply needle and corresponding to the recessed parts respectively in still other embodiments of the black ink cartridge according to the present invention;

Figs. 22(a) to 22(c) are side sectional view showing other embodiments of the ink cartridge constructed in accordance with the invention;

0912073-054399
Figs. 23(a) and 23(b) are respectively a top plan view showing a state in which a lid is detached in the other embodiment of the ink cartridge and a side sectional view viewed along a line A-A of FIG. 23(a);

Figs. 24(a) to 24(c) are respectively an enlarged top plan view showing the area of a cartridge in the vicinity of an ink supply port in accordance with the other embodiment of the ink cartridge and sectional views viewed along lines B-B of FIG. 24(b) and C-C of FIG. 24(c);

Fig. 25(a) is a side sectional view of an ink cartridge showing a state in which one ink housing chamber of the above ink cartridge is filled with ink, and Fig. 25(b) is a front sectional view showing the ink cartridge cut along a line E-E in Fig. 25(a);

Fig. 26 is a top plan view showing the structure of a lid suitable for the ink cartridge shown in Figs. 25(a) and 25(b) in a state in which a film is peeled;

Fig. 27 is a perspective view showing a rear side of the lid shown in Fig. 26;

Figs. 28(a) to 28(d) respectively show the structure of the upper surface of the ink cartridge, sectional structure viewed along lines D-D and E-E and the structure of the rear of the lid;

Fig. 29 is a sectional view showing the structure of another type of ink cartridge to which the present invention can be applied;

Fig. 30 shows another embodiment of fine grooves formed on a lid in accordance with the invention;

Fig. 31 is a side sectional view showing an ink cartridge which is packed under a vacuum condition; and

Fig. 32 is a perspective view showing an ink cartridge with two separate sealing films according to an arrangement of the invention.

PREFERRED EMBODIMENTS OF THE INVENTION

The detailed description of the preferred embodiments of the present invention will now be described herein below with reference to the accompanying drawings.

Fig. 1 shows a printing mechanism equivalent to an embodiment of a printing apparatus for executing printing using an ink cartridge according to the present invention. A carriage 3 is reciprocally mounted within a frame 200 and operatively connected to a driving motor 2 via a timing belt 1. A cartridge holder 6, mounted on carriage 3, for mounting thereon both a black ink cartridge and a color ink cartridge respectively is provided with pivotable levers 4 and 5. A print head 23 to which ink is supplied from each ink cartridge is provided on the lower surface of carriage 3.

Figs. 2 and 3 show an embodiment of the cartridge holder 6 mounted on carriage 3 and in this embodiment, a color ink cartridge housing chamber 7 and a black ink cartridge housing chamber 8 are formed on a bottom 202 of cartridge holder 6. Ink supply needles 10 and 11 respectively communicating with the print head 23 are planted in respective positions opposite to the respective ink supply ports of the ink cartridges which are properly installed.

Rectangular recessed sections 21 and 22 are formed so that they respectively surround the periphery of these ink supply needles 10 and 11. In the vicinity of the ink supply needles 10, projections 12, 13, 14, 15 and 16, each tip end 12a, 13a, 14a, 15a, and 16a of which is slightly higher than that of each ink supply needle 10, are formed approximately along the

walls of the recessed part 21, at four corners of an area in which the ink supply needles 10 are arranged so that the bottom of the ink cartridge can be horizontally supported.

In the meantime, in the vicinity of the ink supply needle 11, first and second projections 18 and 19, each upper end 18a and 19a of which is slightly higher than the end of the ink supply needle 11, are formed so that the ink supply needle 11 is put between the projections. A third projection 20 is formed in the center of floor 202 within chamber 8. The second projection 19 is formed wider to the extent that the bottom of the ink cartridge can be horizontally supported when the ink cartridge is installed in a wrong direction.

Figs. 4(a), 5(a) and 5(b) show the structure of the rear side of cartridge holder 6. A passage forming part 26 is formed on bottom 202 defines the recessed sections 21, 22 within cartridge 6 communicating passages 24 and 25 for connecting each of the ink supply needles 10 and 11 and the print head 23 protrude from bottom 202. The upper surface of bottom 202 is sealed by a sealing plate 27 and the print head 23 is laminated and fixed on the upper surface of bottom 202.

In the passage forming part 26, caulking ribs 26a are formed together with the communicating passages 24, 25 by injection molding and the like as shown in Figs. 5(a), 5(b). Through holes 28 and 29 respectively connecting to the print head and caulking holes 28a are also formed on the sealing plate 27 and both are fixed to carriage 6 in a fluid-tight state by caulking. The print head 23 is mounted on the sealing plate in a state in which its ink inlets respectively communicate with the through holes 28 and 29 of the sealing plate.

Figs. 6(a) to 6(c) are perspective views showing an embodiment of a color ink cartridge. The color ink cartridge 206 is formed as a container 32 on one side of which ink

supply ports 30 where the ink supply needles 10 of the printing apparatus are respectively inserted are formed. The opposite open face container 32 is sealed by a lid 31, and a porous body impregnated with ink is housed inside the color ink cartridge 206.

Ink inlets 33 and air communicating ports 34 are formed on the surface of the lid 31 and each air communicating port 34 is connected to one end of a fine, circuitous groove 36 sealed by a sealing film 35. The fine groove 36 generates the capillary action. The other end of the fine groove 36 communicates with an air communication opening 39 formed in a recessed part 38. As shown in Fig. 8, the recessed part 38 is connected with the other end of the fine groove 36 through a communicating (or tunnel) passage 37 formed as a through hole and extends approximately horizontally inside the thickness of the lid 31. According to an arrangement, the tunnel passage 37 is designed to incline from the air communication opening 39 formed in the recessed part 38, so that no part of the air communication passage, including fine groove 36, tunnel passage 37 and the recessed part 38 does pass in the interior side of the lid 31 of the ink cartridge. In other words, the depth of tunnel 37 is shorter than the thickest part of lid 31.

As shown in Fig. 6(c), the sealing film 35 has a size which is equal to or slightly smaller than an area defined by a rectangular recess 231 formed in the edge of the lid 31, so that the four edges of the sealing film 35 are bent down into the recess 231. Owing to the design, the sealing film 35 is hardly peeled off when a user touches the ink cartridge when mounted on the printer.

A recessed part 40 for fitting to the projection of a lever 4 is formed on the center line of the lid 31 and a recessed part 41 for securing negative-pressure volume is formed in a residual part of lid 31. The recessed parts 38 are completely sealed by a film 42, one end 42a of

which is extended outside the lid 31 which can be peeled. The recessed parts 40 and 41 are partly sealed by the same film 42 in a state in which openings 40a and 41a for communicating with the air are formed respectively in a portion of recessed parts 40, 41 which remains uncovered.

A convex portion 48 which is adapted to touch to the inner wall of the recessed part 21 of the cartridge holder 6 when the cartridge is properly positioned in cartridge 6 protrudes from bottom 43. Cartridge 6 is provided with a shape into which the convex portion can be inserted. Ink supply ports 30 for respectively fitting to the ink supply needles 10 are provided at the convex portion 48. Recessed parts 44-47 formed on bottom 43 for receiving projections 12 to 16 on the side of the cartridge holder 6. Recessed parts 44-47 are formed so that these ink supply ports 30 are put between the diagonal points of an imaginary quadrilateral.

A black ink cartridge 208 includes a container 52 on one side of which an ink supply port 50, where the ink supply needle 10 of the printing apparatus is inserted, is formed. The opposite open face of container 52 is sealed by a lid 51 as shown in Figs. 7(a)-(c). A porous body impregnated with ink is housed inside the black ink cartridge 208.

An ink inlet 53 and an air communicating port 54 are formed on the surface of the lid 51. Air communicating port 54 is connected to one end of a fine groove 56 sealed by a film 55 to form a capillary. The other end of the fine groove 56 communicates with an opening 59. Opening 59 communicates with a recessed part 58, formed on the side of the other end. Passage 57 is formed as a through hole and extends approximately horizontally inside the lid 51 as shown in Fig. 8. Each through hole respectively forming the above communicating passages 37 and 57

is tilted so that each side of the recessed parts 38 and 58 is slightly higher so as to enable puffing out a pin in injection molding.

A recessed part 60 for fitting to the projection of the lever 5 is formed on the center line of the lid 51 and a recessed part 61 for securing negative-pressure volume is formed in a residual part.

The recessed part 58 is completely sealed by a film 62, one end 62a of which extends beyond an edge of the lid 51, and can be peeled off when used. The recessed part 60 is partly sealed by the same film 62 in a state in which a part 60a communicates with the air. The recessed part 61 communicates with the recessed part 60 via a recessed part 61a.

As described above, even if the ink cartridge is packed and vacuumed, a package having film 42 or 62 sealing the recessed part 41 or 60 in a state in which space for decompression can be prevented from being blocked by the package. Specifically, when the ink cartridge is enclosed in a flexible package 180, such as an aluminum layered package, or vinyl made package and sealed under vacuum condition as shown in Fig. 31, air transfer occurs between the ink chamber 137 and the recessed parts 145 formed on the lid of the cartridge. That is, gas contained in ink or gas generated when ink component is dissolved moves into the recessed parts 145. Accordingly, no air bubble would be created in the ink even when the ink cartridge is stocked in a warehouse for a long time.

In the meantime, on the side of container 52 opposite to the lid 51, a convex portion 67 protrudes from bottom 63 and is provided with a shape approximately equivalent to the inner wall of the recessed part 22 of the cartridge holder 6. The ink supply port 50, for fitting to the ink supply needle 11, is provided in the convex portion 67. Recessed parts 64 and 65 are

formed at the front side and the rear side of the ink supply port 50 in such a manner that the ink supply port 50 is located between the recessed parts 64 and 65. Recessed parts 64 and 65 receive projections 18, 19 and 20 on cartridge holder 6.

Next, a process for inserting the ink cartridge composed as described above will be described by the example of the black ink cartridge to simplify the description.

When an ink cartridge K is taken out of a package which maintains the cartridge under negative pressure in the process of distribution, and the film 62 which can be peeled off is removed, the air communicating opening 59 becomes open to the air and the recessed part 60 is also exposed. If the black ink cartridge K is installed in a proper direction of the cartridge holder 6, the recessed parts 64 and 65, formed on the bottom 63, are opposed to the projections 18 to 20 of the holder 6 as shown in Fig. 9a.

When the lever 5 attached to the holder 6 is operated in this state, the projection 5a of the lever 5 is received by the recessed part 60 of the lid 51. Lever 5 pushes down the cartridge K. In the process of push down, the projections 18, 19 and 20 of the holder 6 are respectively first fitted into the recessed parts 64 and 65 of the cartridge K and the cartridge K is guided to a normal position by a slant face of tip 18a formed at the end and a tapered part of tip 20a.

When the cartridge K is further pushed down, the ink supply needle 11 pierces the film 66 sealing the ink supply port 50 and is inserted into the ink supply port 50 as shown in Fig. 9b. The lever 5 is pivoted to a normal position and a fitting part 5b slides past and is fixed to a hook 3a of the carriage 3. As the convex portion 67, in which the ink supply port 50 is formed, is fitted into the recessed part 22 of the cartridge holder 6 and caught, the printing apparatus is

prevented from rattling due to vibration and the like when the cartridge K is installed in a proper position, and the leakage of ink and the application of unnecessary external force to the ink supply needle are securely prevented.

As the projection 5a of the lever 5 comes into abutment against the film 62 and lifted, as shown in Fig. 10a, even if the ink cartridge K is installed in a proper posture when film 62 has not been peeled projection 5a is stopped and the fitting part 5b does not reach the hook 3a of the carriage 3 and the lever 5 cannot be fixed to the carriage 3. If a user notices it, he or she peels off the left film 62 and reinstalls the ink cartridge K. Therefore, a failure of ink supply during printing caused because a user forgets to peel the film 62 can be prevented beforehand.

In the meantime, if the black ink cartridge K is installed in the improper way as shown in Fig. 10b, the bottom 63 is opposed to the wide projection 19 and is supported in a position higher than the end of the ink supply needle 11 in an approximately horizontal posture. As the ink cartridge K does not lower due to the projection 19 even if the lever 5 is turned in this state, the ink supply needle 11 is prevented from being broken.

In the case of the color ink cartridge, printing in a state in which the film 42 is not peeled is also prevented by the similar action and if the color ink cartridge is installed in a wrong direction, the breakage of the ink supply needle 10 is prevented because the projection 12 comes first into abutment against the bottom 43 and prevents the bottom from lowering.

In the above embodiments, the films 35 and 55 forming a capillary together with the fine groove 56 and the films 42 and 62 which are peeled to provide communication with the air during use are respectively independently stuck on the lids 31 and 51. However, even if an integrated film 70 in which an area 70a forming a capillary and an area 70b to be removed in use

are connected via a narrow part 70c which can be torn off as shown in Fig. 11a, or a film 71 forming a capillary and a film 72 to be peeled off overlapping with the film 71 in a part 71a as shown in Fig. 11b are respectively stuck, the similar action is produced. Further, if a second film 71' is affixed as shown in Fig. 11c so that the surface of the lid is at least covered in the area 70a forming a capillary, ink can be securely prevented from being evaporated.

According to another arrangement of the invention, as shown in Fig. 32, a first sealing film 76 covers fine, circuitous grooves 34 formed on a lid 31 of the ink cartridge 132 whereas a second sealing film 77 covers entire surface of the lid 31 over the first sealing film 76 not only air communication holes 39. The second sealing film 77 may be peeled off when the ink cartridge is in use. The first sealing film 76 and the second sealing film 77 may have different colors from each other or formed from different material. This arrangement may be advantageous in that a user can easily recognize that which sealing film is to be peeled off.

Also, in the above embodiments, the communicating passages 37 and 57 are respectively formed as a through hole approximately horizontally extending, though it is slightly tilted. However, even if one end of a fine groove 36 composing a capillary pierces a lid 31, a fine, circuitous groove 74 is formed so that the fine groove 36 communicates with a recessed part 38 for opening to the air and the fine groove 74 is covered by a sealing film 75 as shown in Fig. 12, the similar action is produced. According to this embodiment, when through holes to the communicating passages 37 and 57 are formed, work for inserting/extracting a pin required in an injection molding process is not required and a process for forming the lid can be simplified.

As shown in FIG. 13, in a second embodiment, the recessed part 65 for fitting to the projection 19 is integrated with the recessed part for fitting to the projection 20 to install or

detach the cartridge K in or from the carriage or the cartridge holder 6 by a mechanism in which a lifter 176 connects to the lever 105 via an operating rod 175 as shown in Fig. 13. In the present embodiment, the lifter 176 is guided up and down along a guide groove 177 by the operation of the lever 105, so that the ink cartridge is attached to or detached from the cartridge holder 106. In the operation, the projection 19 engages with and disengages from one recessed part 65a of the ink cartridge so that the ink cartridge can be accurately positioned as mentioned above. However, in the case of an ink cartridge mounted or detached by a lever not provided with the lifter 176, even if recessed parts 64 and 65 are formed as shown in Figs. 14(a), 14(b), so that a convex portion 67, in which the ink supply port 50 is formed, is located between the recessed parts 64, 65 and a recessed part 73 is independently formed in a position opposite to the convex portion 20 of the cartridge holder, the similar action is produced.

Reference is now made to FIGS. 15(a) and 15(b) in which another embodiment of the invention is provided. Ink cartridge 212 paired with such a black ink container, it is desirable that recessed parts 68 are formed along one wall of a convex portion 48 in which the ink supply port 30 is formed and on the side of the cartridge so that as a large interval as possible is provided between recessed parts 68. A recessed part 69 is formed on the other side, across the convex portion 48, so that the recessed part 69 is opposite to at least one recessed part 68.

As described above, if the relationship between another member and the recessed part is not required to be considered, recessed parts 68 and 69 are located at the diagonal points of a convex portion 48 as shown in Fig. 16(a), and formed so that they are close to the wall of the convex portion 48 in a color ink cartridge. Convex portions 12' and 15' may also be formed in the color ink cartridge housing chamber 7 of the holder 6 so that the convex portions 12', 15'

respectively correspond to the recessed parts 68 and 69. If necessary, in yet another embodiment a recessed part 69' may be also formed at a center position along the wall, on which no recessed part exists, of the convex portion 48 where the ink supply port 30 is formed with the recessed part 69' close to the wall of the convex portion 48 as shown in Fig. 17(a).

A convex portion 12" corresponding to the recessed part 69' is formed in holder 6 corresponding to the above ink cartridge. Hereby, the ink cartridge can be more securely prevented from being improperly inserted by the convex portions 12', 12" and 15' arranged around the ink supply needle 10.

The above embodiment relates to the color ink cartridge, however, as for a black ink cartridge paired with it, embodiments shown in Figs. 18(a) to 21(b) are also desirable.

That is, in an embodiment shown in Fig. 18(a), recessed parts 64 and 65 are located at the diagonal points of a convex portion 67 and formed so that they are close to the wall of the convex portion 67, while convex portions 18' and 19' are formed corresponding to these recessed parts 64 and 65 in the ink cartridge housing chamber 8 of the holder 6 as shown in Fig. 18(b). A pair of adjacent recessed parts 64 and a pair of adjacent recessed parts 65 are located at diagonal points as shown in the embodiment of Fig. 19(a), while convex portions 18' are formed adjacently and convex portions 19' are formed adjacently respectively corresponding to the recessed parts 64 and 65 as shown in Fig. 19(b) in the ink cartridge housing chamber 8 of the holder 6. Further, as shown in the embodiment of Fig. 20(a), recessed parts 64 and 65 may be also formed in the shape of a hook so that they surround the corners of a convex portion 67 and convex portions 18' and 19' may be also formed in the shape of a hook as shown in Fig. 20(b).

Further, as shown in Fig. 21(a), recessed parts may also be formed on a center line passing an ink supply port 66 so that they surround the four sides of a convex portion 67 and corresponding to these, convex portions 18' and 19' may be also arranged on a center line passing the ink supply needle 11 in the cartridge housing chamber 8.

Three colors of ink of at least cyan, magenta and yellow, or four colors of ink if including black, are normally used for color printing. However, to improve the printing quality, cyan and magenta may be classified into two systems of a dark type and a light type. Therefore, a color ink cartridge may be divided into five ink housing chambers and each chamber may be filled with ink of cyan, magenta and yellow which belong to the dark type and ink of cyan and magenta which belong to the light type.

A cartridge 80 for applying the different types of ink is now described in FIGS. 22(a)-22(c). Ink cartridge 80 includes ink housing chambers 81-85. A respective ink supply port 86-90 is provided in a respective ink housing chamber 81-85. As ink of each color is consumed differently in color printing, the volume of each ink housing chambers 81 to 85 of a cartridge 80 shown in Fig. 22a are not equal. More specifically, the width w1 to w5 of each housing chamber is designed to be different from one another to fix the ink consumption rate of the whole ink cartridge. In the meantime, each print head to which ink is supplied from each chamber is arranged at fixed pitch in consideration of control and others in printing and therefore, the arrangement pitch of ink supply needles integrated with each print head is also fixed.

Therefore, if ink supply ports 86 to 90, respectively communicating with the ink housing chambers 81 to 85 of the ink cartridge 80, are formed on the center line c1 to c5 of each chamber, there arises a problem that mis-position is caused between each ink supply needle and

each ink supply port of the cartridge, the ink cartridge cannot be installed and the ink supply needle is broken.

Fig. 22a shows an embodiment of an ink cartridge to solve these problems and although ink output ports 86 to 90 of ink housing chambers 81 to 85 are arranged on each center line c1 to c5 of the ink housing chambers 81 to 85, ink supply ports 91 to 95 are arranged according to the arrangement pitch S of ink supply needles, and the ink output ports and the ink supply ports are respectively connected via passages 96 to 100 in the shape of a crank. According to this embodiment, the ink consumption rate of each ink housing chamber of the cartridge can be adjusted so that it is approximately equal and in addition, fitting to or detaching from the ink supply needle can be smoothly executed.

In the above embodiment, an ink consumption rate in the ink cartridge 80 is approximately equalized, however, if an ink consumption rate may be uneven, ink supply ports 91 to 95 are arranged according to the arrangement pitch S of ink supply needles and ink housing chambers 81' to 85' are formed so that each center is located on each center line of the ink supply ports 91 to 95, while a gap made between the cartridge and the cartridge holder 6 may also be adjusted by projections 101 and 102 provided on the side (Fig. 22(b)) and may also be adjusted by adjusting the thickness d of at least one side wall 103 of the ink cartridge (Fig. 22(c)).

If each ink housing chamber 81 to 85 is narrow as described above, the discharge of ink from a porous body impregnated with ink and housed in each ink housing chamber 81 to 85 to each ink supply port 91 to 95 is difficult, compared with an ink cartridge provided with wide ink housing chambers.

Reference is now made to FIGS 23(a), 23(b) in which an embodiment of the invention to solve the above problems is provided. An ink cartridge 280 includes a plurality of ink housing chambers 81-85. A respective ink supply port 91-95 is provided in each housing chamber 81-85. It is desirable that a slant part 106 wider on the side of the ink housing chamber from the side of the ink supply port 93 is formed in a protruding part 105 which protrudes toward the ink housing chamber 83. A filter 104 is affixed to projection 104 as shown in Fig. 23(b). The slant part 106 may be arcuated if desired, so that air bubbles may be guided more effectively to the ink supply port 93.

Further, when an elongated convex portion 108 is formed on a recessed part 107 formed between the protruding part 105 and the filter 104 as shown in Figs. 24(a)-(c), where protruding part 105 is relatively narrow as shown in Fig. 23(b), the filter 104 can be prevented from being bent by the pressure of a porous body housed in the ink housing chamber 83 and ink can be made to flow smoothly to the ink supply port 92 by the capillary force of a fine groove generated by the convex portion 108.

A porous body 109 impregnated with ink as shown in Fig. 25(a) is originally disposed in each ink housing chamber 81 to 85 (the ink housing chamber 82 is represented in Fig. 25(a) of such an ink cartridge so that the porous body is touched to the filter 104 as shown in Fig. 25(b) and is sealed by a lid 110.

In the ink cartridge 80 in which multiple ink housing chambers 81-85 are formed as described above, it is difficult to form a fine, circuitous groove to function as a capillary having large fluid resistance on the lid 110. That is, to increase fluid resistance, the cross section of the fine groove has only to be reduced, however, there is a problem that clogging is caused by

dust and the like and ink is not supplied in printing. Therefore, as the cross section to some extent is required, fluid resistance is required to be secured by the length of the fine groove.

Figs. 26 and 27 are views showing an embodiment of a cartridge lid 110 designed in view of the foregoing problems. Lid 110 includes air communicating ports 111 and 111' ink inlets 112 and fine grooves 113. A respective end of fine grooves 113 communicates with each air communicating port 111, 111' which are formed so that they communicate with each ink housing chamber 81-85. As shown in Fig. 27, vertical ribs 117 are formed in the inner face of the lid 110. The both the ends of the vertical ribs 117 perform to guide the cartridge lid 110 into the cartridge body when the lid 110 is coupled to the cartridge body. Because an upper-outer corner of the vertical rib 117 is chamfered to have an angled surface, the lid 110 can smoothly be coupled to the cartridge body while guided by the angled surface of the rib 117.

The fine groove 113 is formed in an area opposite to each ink housing chamber where no air communicating port 111 or 111' and no ink inlet 112 in the above capillary forming area exist so that the fine groove meanders plural times and the fine grooves respectively communicate with openings 114 and 114' for communicating with the air via communicating areas 113 and 113' having the similar structure to the communicating passages 74 shown in Fig. 12.

As clear from the above description, lid 110 may be divided into an area F in which the fine grooves 113 and 113' are formed is sealed by a film which cannot be peeled off by a user and an area G of the openings 114 and 114' for communicating with the air is sealed by a film which can be peeled by a user. Plural recessed parts 115 for securing volume are formed on the side on which the openings for communicating with the air 114 and 114' are formed and if

necessary, a recessed part 116 for fitting to the projection 5a shown in Fig. 9 of the lever 5 is also formed.

If the lid 124 is formed by injection molding, a so-called shrink is easily caused in an area where the fine groove 113 is formed. In the meantime, as for the ink cartridge, a porous body 121 impregnated with ink is housed in an ink housing chamber 120 as shown in Fig. 28b so that the porous body 121 is touched to a filter 123 of an ink supply port 122. In this case, slight space 126 is secured by a rib 125 on the rear of a cap 124 to prevent ink from leaking due to the rapid change of temperature.

Therefore, it is desirable that the above rib 125 is formed so that the rib is opposite to a fine groove 129 connecting an air communicating port 127 and an opening open to the air 128 respectively of the lid 124. A reference number 131 denotes a recessed part for fitting to the projection 5a shown in Fig. 9 of the lever 5.

In the above embodiments, a porous body impregnated with ink is housed in the whole ink housing chamber, however, even if the present invention is applied to an ink cartridge wherein one ink housing chamber is divided into two chambers 134 and 135 by a partition 133 at the bottom of which a communicating port 132 is provided as shown in Fig. 29, a porous body 137 impregnated with ink is housed on the side of an ink supply port 136 and ink 138 is housed in the other chamber 135, a similar action is produced.

Also, in the above embodiments, the fine, circuitous groove creating a capillary action connects to the opening for communicating with the air via the tunnel-like communicating passage formed on the lid however, even if fine grooves 141 respectively connected to air communicating ports 140 of plural ink housing chambers are made to meander so that the fine

groove is opposite to the above ink chamber in a central area in which the air communicating ports 140 and ink inlets 142 are formed, are collected with each independent on the side of the other end and are respectively connected to openings for communicating with the air 144 sealed by a film which can be peeled in a very narrow area 143, recessed parts 145 for securing decompression space can be formed in relatively large size as shown in Fig. 30.

It will thus be seen that the objects set forth above, among those made apparent from the preceding description, are efficiently attained and, since certain changes may be made in the above construction without departing from the spirit and scope of the invention, it is intended that all matter contained in the above description or shown in the accompanying drawing shall be interpreted as illustrative and not in a limiting sense.

It is also to be understood that the following claims are intended to cover all of the generic and specific features of the invention herein described and all statements of the scope of the invention which, as a matter of language, might be said to fall therebetween.

WHAT IS CLAIMED IS:

1. An ink cartridge for an ink jet printer, comprising:
a housing having at least one wall;
at least two ink chambers for containing different ink accommodated in said housing;
and
ink supply ports formed in one wall of said housing within each of said ink chambers,
each of said ink supply ports having an inner opening and an outer opening,

wherein a first distance from said inner opening of a first ink supply port to that of a
second ink supply port adjacent to said first ink supply port is different from a second distance
from said outer opening of said first ink supply opening to that of said second ink supply port.
2. The ink cartridge of claim 1, wherein said first distance is greater than said second
distance.
3. The ink cartridge of claim 1, further comprising:
ink supply passages at least partly defining said ink supply port, each of said ink supply
passage projecting inward said housing from a bottom wall of said housing, said ink supply
passage communicating with said respective ink chamber at an inner end thereof; and
porous members impregnated with ink and fitted in each of said ink chambers and
engaging with said ink supply port through said ink supply passage.
4. The ink cartridge of claim 1, wherein said ink chamber comprises three chambers
separated from one another.

5. The ink cartridge of claim 1, wherein said ink chamber comprises five chambers separated from one another.

6. The ink cartridge of claim 3, wherein said each of said ink supply port compresses said respective porous member.

7. The ink cartridge of claim 3, wherein each of said ink supply passages is disposed at substantially a center of said respective ink chamber.

8. An ink cartridge for an ink jet printer, comprising:
a housing having at least one wall;
at least one ink chamber for containing ink accommodated in said housing;
and
an ink supply port formed in one wall of said housing said ink supply port having an inner opening and an outer opening, said ink supply port comprising at least one angled inner surface.

9. The ink cartridge of claim 6, wherein said angled surface is arcuated.

10. The ink cartridge of claim 6, wherein said inner surface of said ink supply port is entirely angled.

11. An ink cartridge for an ink jet printer, comprising:
a housing having at least one wall;
at least one ink chamber for containing ink in said housing;
an ink supply port formed in one wall of said housing at an end of said ink chamber, said ink supply port having an inner opening and an outer opening;

ink supply passages at least partly defining said ink supply port, each of said ink supply passage projecting inward said housing from a bottom wall of said housing, said ink supply passage communicating with a respective ink chamber at an inner end thereof, said ink supply passage comprising a recessed part formed at a top thereof and a projecting edge surrounding said recessed part, said ink supply passage further comprising at least one protrusion member formed on said recessed part isolated from said projecting edge and a filter disposed on said projecting edge and said protrusion member; and

at least one porous member impregnated with ink, and fitted in each of said ink chambers and engaging with said ink supply port through said ink supply passage.

12. The ink cartridge of claim 9, wherein the height of said protrusion member is higher than that of said projecting edge when said filter is secured onto said projecting edge.

13. The ink cartridge of claim 9, wherein said protrusion member comprises two or more elongated protrusions.

14. The ink cartridge of claim 11, wherein said elongated protrusions extend toward said ink supply port which opens in said recessed part.

15. An ink cartridge for an ink jet printer, comprising:
a housing having walls and an opening, a top wall of said housing being constituted by a lid covering said opening of said housing;
at least one ink chamber defined by said housing and said lid;
an ink supply port formed on one of the walls of said housing;

at least one recess forming a space in an outer surface of said lid, the pressure within said space being lower than the atmospheric pressure when the ink cartridge is packed.

16. The ink cartridge of claim 15, further comprising a seal member, wherein said wall has an outer surface, the recess being covered by said seal member adhered onto the outer surface of the wall of said housing.

17. The ink cartridge of claim 16, wherein a portion of said seal member is removable, and said recess is disposed under the removable portion of said seal member.

18. The ink cartridge of claim 17, wherein said recess is disposed on a part of said lid which is spaced apart from said ink supply port.

19. The ink cartridge of claim 15, wherein the ink jet printer includes a carriage, the cartridge being mounted in the carriage and said recess is disposed on a part of said lid which is engageable with a member of the carriage when the ink cartridge is mounted on the carriage.

20. The ink cartridge of claim 19, further comprising a mounting lever mounted on the carriage wherein the member of the carriage comprises a rod projecting from the mounting lever.

21. The ink cartridge of claim 16, wherein plural number of said recesses are formed in the outer surface of said lid.

22. The ink cartridge of claim 15, further comprising a fine, circuitous groove formed in one surface of said lid where said recess is formed.

23. The ink cartridge of claim 15, further comprising an air communication hole formed in said lid for communicating the interior of the ink cartridge with the atmospheric air, said air communication hole being disposed in the vicinity of said recess.

24. An ink cartridge for an ink jet printer, comprising:

- a housing having a bottom wall and an opening;
- an ink supply port formed on the bottom wall;
- a through hole formed in said lid and connecting the inside and outside of the ink cartridge;
- an air vent section formed on said lid which communicates with atmospheric air when the ink cartridge is in use;
- a circuitous channel formed in an outer surface of said lid and connecting said through hole to said air vent section, said circuitous channel comprising a tunnel part which is a hole formed in said lid;
- a first seal member affixed to said lid over said through hole and one part of said circuitous channel; and
- a second, removable seal member affixed to said lid over said air vent section, said second seal member being removed when the ink cartridge is in use.

25. The ink cartridge of claim 24, wherein said second seal member is spaced apart from said first seal member for defining a non-sealed portion, and said non-sealed portion of said lid is disposed over said tunnel part of said circuitous channel.

26. The ink cartridge of claim 24, further comprising a groove formed in an inner surface of said lid and connecting to said tunnel part of said circuitous channel.

27. The ink cartridge of claim 26, further comprising a third seal member affixed to the inner surface of said lid covering said groove.

28. The ink cartridge of claim 24, wherein said tunnel part of said circuitous channel is inclined to connect directly to said air vent section, and the depth of said tunnel part is shorter than the thickest part of said lid.

29. The ink cartridge of claim 24, further comprising ribs formed on the inner surface of said lid at portions thereof corresponding to said circuitous channel.

30. The ink cartridge of claim 24, further comprising a plurality of ink chambers for containing different inks therein, said ink chambers being formed within said housing, and a plurality of said circuitous channels and said through holes a respective circuitous route and through hole corresponding to a respective one of said ink chambers.

31. The ink cartridge of claim 30, wherein the ink cartridge comprises three ink chambers, three circuitous channels and one air vent section connecting to all the three circuitous channels.

32. The ink cartridge of claim 30, wherein the ink cartridge comprises five ink chambers, five circuitous channels and two air vent sections connecting to at least two of said five circuitous channels.

33. The ink cartridge of claim 24, further comprising a porous member fitted within an ink chamber defined by said housing and said lid, said porous member being impregnated with ink.

34. The ink cartridge of claim 24, further comprising a recess formed in the outer surface of said lid, and said air vent section being formed within said recess.

35. The ink cartridge of claim 34, wherein an opening of said air vent section is formed in a side wall of said recess.

36. An ink cartridge for an ink jet printer said ink jet printer having a member and ink supply needle, comprising:

a housing having at least one wall;

an ink supply port formed on the wall of said housing; and

at least one engaging hole means formed in the wall of said housing adjacent to said ink supply port, said engaging hole means being engageable with the member of the printer when the ink cartridge is mounted on the printer.

37. The ink cartridge of claim 36, wherein said engaging hole means engages with a projection formed on the ink jet printer, the height of the projection being greater than that of the ink supply needle of the ink jet printer.

38. The ink cartridge of claim 37, further comprising an abutment member which abuts against the projection of the ink jet printer when the ink cartridge is mounted in the improperly.

39. The ink cartridge of claim 37, wherein the projection extends from a lever of a cartridge holder of the ink jet printer.

40. The ink cartridge of claim 36, wherein said ink supply port and said engaging hole means are formed on a bottom of said housing.

41. The ink cartridge of claim 40, wherein said ink supply port protrudes from the bottom wall of said housing.

42. The ink cartridge of claim 36, wherein said engaging hole means comprises an odd number of engaging holes.

43. The ink cartridge of claim 36, wherein said engaging hole means comprises an even number of engaging holes.

44. The ink cartridge of claim 42, wherein the position of said engaging holes are asymmetrical with respect to a center transversal line of said ink supply port.

45. The ink cartridge of claim 42, wherein at least two of the engaging holes are disposed along a line.

46. The ink cartridge of claim 43, wherein at least two of the engaging holes are disposed along a line.

47. The ink cartridge of claim 36, wherein said engaging hole means is rectangular in cross section.

48. The ink cartridge of claim 46, wherein a second engaging recess is formed on an outer surface of said lid.

49. The ink cartridge of claim 47, further comprising a porous member fitted in an ink chamber defined by said housing and said lid, said porous member being impregnated with ink and engaging with said ink supply port.

50. The ink cartridge of claim 46, further comprising a seal member affixed to an outer surface of said lid, a portion of said seal member being removable.

51. The ink cartridge of claim 46, wherein said lid has a center line, and said engaging recess is disposed at a position which deviates from the center line of said lid.

52. The ink cartridge of claim 46, wherein said engaging recess has capacity sufficient to receive gas escaped from the ink cartridge when the ink cartridge is packed in a package under a degassed condition.

53. The ink cartridge of claim 46, wherein the engaging recess engages with a rod projecting from a carriage of the printer onto which the ink cartridge is mounted.

54. The ink cartridge of claim 46, wherein said engaging recess is covered by a removable seal.

55. The ink cartridge of claim 46, wherein said cartridge holder includes a lever, said engaging recess engaging with a projection formed on a lever of a cartridge holder of the ink jet printer.

56. The ink cartridge of claim 55, wherein said engaging recess comprising a first section for receiving the projection of the lever and a second section for receiving the member of the printer, and said first section and said second section being formed continuously.

57. An ink cartridge for an ink jet printer, comprising:
a housing having a wall and an opening,
a lid covering said opening of said housing;
an ink supply hole formed on said wall of said housing; and
at least one engaging recess formed on said wall of said housing, said engaging recess being engageable with a member of the printer when the ink cartridge is correctly mounted on the printer.

58. An ink jet printer, comprising:
a carriage, said carriage having a member extending therefrom;
a print head including a plurality of nozzles through which ink is ejected mounted on said carriage;
an ink cartridge, said ink cartridge being mounted on the carriage and, said ink cartridge comprising:
a housing having walls and an opening, a top wall of said housing being constituted by a lid covering said opening of said housing;
at least one ink chamber defined by said housing and said lid;
an ink supply port formed on one of the walls of said housing;

at least one recess forming a space in an outer surface of said lid and engagable with said member when the ink cartridge is mounted on the carriage, the pressure within said space being lower than the atmospheric pressure when the ink cartridge is packed.

59. The ink cartridge of claim 58, further comprising a seal member, wherein said wall has an outer surface, the recess being covered by said seal member adhered onto the outer surface of the wall of said housing.

60. The ink cartridge of claim 58, further comprising a mounting lever mounted on the carriage wherein the member of the carriage comprises a rod projecting from the mounting lever.

61. The ink cartridge of claim 59, wherein plural number of said recesses are formed in the outer surface of said lid.

62. An ink jet printer, comprising:
a carriage, said carriage having a member extending therefrom;
a print head including a plurality of nozzles through which ink is ejected mounted on said carriage;

an ink cartridge, said ink cartridge being mounted on the carriage and, said ink cartridge comprising:

a housing having at least one wall;

an ink supply port formed on the wall of said housing; and

at least one engaging hole means formed in the wall of said housing adjacent to said ink supply port, said engaging hole means being engageable with the member of the printer when the ink cartridge is mounted on the carriage.

63. The ink cartridge of claim 62, wherein said engaging hole means engages with a projection formed on the ink jet printer, the height of the projection being greater than that of the ink supply needle of the ink jet printer.

64. The ink cartridge of claim 63, further comprising an abutment member which abuts against the projection of the ink jet printer when the ink cartridge is mounted in the improperly.

65. The ink cartridge of claim 63, wherein the projection extends from a lever of a cartridge holder of the ink jet printer.

66. The ink cartridge of claim 62, wherein said ink supply port and said engaging hole means are formed on a bottom of said housing.

67. The ink cartridge of claim 66, wherein said ink supply port protrudes from the bottom wall of said housing.

68. The ink cartridge of claim 62, wherein said engaging hole means comprises an odd number of engaging holes.

69. The ink cartridge of claim 62, wherein said engaging hole means comprises an even number of engaging holes.

70. The ink cartridge of claim 68, wherein the position of said engaging holes are asymmetrical with respect to a center transversal line of said ink supply port.

71. The ink cartridge of claim 68, wherein at least two of the engaging holes are disposed along a line.

72. The ink cartridge of claim 69, wherein at least two of the engaging holes are disposed along a line.

73. The ink cartridge of claim 62, wherein said engaging hole means is rectangular in cross section.

74. The ink cartridge of claim 72, wherein a second engaging recess is formed on an outer surface of said lid.

75. The ink cartridge of claim 73, further comprising a porous member fitted in an ink chamber defined by said housing and said lid, said porous member being impregnated with ink and engaging with said ink supply port.

76. The ink cartridge of claim 72, further comprising a seal member affixed to an outer surface of said lid, a portion of said seal member being removable.

77. The ink cartridge of claim 72, wherein said lid has a center line, and said engaging recess is disposed at a position which deviates from the center line of said lid.

78. The ink cartridge of claim 72, wherein said engaging recess has capacity sufficient to receive gas escaped from the ink cartridge when the ink cartridge is packed in a package under a degassed condition.

79. The ink cartridge of claim 72, wherein the engaging recess engages with a rod projecting from a carriage of the printer onto which the ink cartridge is mounted.

80. The ink cartridge of claim 72, wherein said engaging recess is covered by a removable seal.

81. The ink cartridge of claim 72, wherein said cartridge holder includes a lever, said engaging recess engaging with a projection formed on a lever of a cartridge holder of the ink jet printer.

82. The ink cartridge of claim 81, wherein said engaging recess comprising a first section for receiving the projection of the lever and a second section for receiving the member of the printer, and said first section and said second section being formed continuously.

ABSTRACT OF THE DISCLOSURE

An ink cartridge for an ink jet printer having a housing having at least one wall. The ink cartridge further has at least two ink chambers for containing different ink accommodated in the housing. Ink supply ports are formed in one wall of the housing within each of the ink chambers. Each of the ink supply ports has an inner opening and an outer opening.

The distance from the inner opening of a first ink supply port to that of a second ink supply port adjacent to the first ink supply port is different from a second distance from the outer opening of the first ink supply opening to that of the second ink supply port.

05312073.051399

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5 (a)




Fig. 5 (b)




Fig. 6 (a)




Fig. 6. (b)




Fig. 6 (c)




Fig. 7 (a)




Fig. 7 (b)




Fig. 7 (c)






Fig. 8







Fig. 10 (a)




Fig. 10 (b)




Fig. 11 (a)




Fig. 11 (b)




Fig. 11 (c)





Fig. 12



05412073-054389

Fig. 13




Fig. 14 (a)




Fig. 14 (b)




Fig. 15 (a)





Fig. 15 (b)






Fig. 16 (a)




Fig. 16 (b)

08412073-051389

Fig. 17 (a)




Fig. 17 (b)




Fig. 18 (a)




Fig. 18 (b)




Fig. 19 (a)




Fig. 19 (b)




Fig. 20 (a)




Fig. 20 (b)




Fig. 21 (a)





Fig. 21 (b)



0541393-0541393

Fig. 22 (a)




Fig. 22 (b)




Fig. 22 (c)




Fig. 23 (a)




Fig. 23 (b)




Fig. 24




Fig. 24




Fig. 24




Fig. 25 (a)




Fig. 25 (b)




Fig. 26




Fig. 27




Fig. 28 (a)




Fig. 28 (b)




Fig. 28 (c)




Fig. 28 (d)




Fig. 29




Fig. 30





FIG. 31


FIG. 31



0941307.061399
66450"6404660

~~【图 1-3】~~

FIG. 32.



Declaration and Power of Attorney For Patent Application

特許出願宣言書

Japanese Language Declaration

私は、下欄に氏名を記載した発明者として、以下のとおり宣言する：

私の住所、郵便の宛先および国籍は、下欄に氏名に続いて記載したとおりであり、

名称の発明に関し、請求の範囲に記載した特許を求める主題の本来の、最初にして唯一の発明者である（一人の氏名のみが下欄に記載されている場合）か、もしくは本来の、最初にして共同の発明者である（複数の氏名が下欄に記載されている場合）と信じ、

その明細書を
(該当する方に印を付す)

☐ ここに添付する。

☐ _____ 日に出願番号

第 _____ 号として提出し、

_____ 日に補正した。
(該当する場合)

私は、前記のとおり補正した請求の範囲を含む前記明細書の内容を検討し、理解したことを陳述する。

私は、連邦規則法典第37部第1章第56条 _____ 項に従い、本願の審査に所要の情報を開示すべき義務を有することを認める。

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

INK CARTRIDGE FOR INK JET PRINTING APPARATUS

the specification of which

(check one)

☒ is attached hereto.

☐ was filed on _____ as

Application Serial No. _____

and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56.

Japanese Language Declaration

私は、合衆国法典第35部第119条にもとづく下記の外国特許出願または発明者証出願の外国優先権利益を主張し、さらに優先権の主張に係わる基礎出願の出願日前の出願日を有する外国特許出願または発明者証出願を以下に明記する：

Prior foreign applications

先の外国出願

Hei. 10-130630	Japan	13/5/98
(Number) (番号)	(Country) (国名)	(Day/Month/Year Filed) (出願の年月日)
Hei. 10-130631	Japan	13/5/98
(Number) (番号)	(Country) (国名)	(Day/Month/Year Filed) (出願の年月日)
Hei. 10-131483	Japan	14/5/98
(Number) (番号)	(Country) (国名)	(Day/Month/Year Filed) (出願の年月日)

Priority claimed

優先権の主張

<input checked="" type="checkbox"/> Yes あり	<input type="checkbox"/> No なし
<input checked="" type="checkbox"/> Yes あり	<input type="checkbox"/> No なし
<input checked="" type="checkbox"/> Yes あり	<input type="checkbox"/> No なし

私は、合衆国法典第35部第120条にもとづく下記の合衆国特許出願の利益を主張し、本願の請求の範囲各項に記載の主題が合衆国法典第35部第112条第1項に規定の態様で先の合衆国出願に開示されていない限度において、先の出願の出願日と本願の国内出願日またはPCT国際出願日の間に公表された連邦規則法典第37部第1章第56条項に記載の所要の情報を開示すべき義務を有することを認める：

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)

(出願番号)

(Filing Date)

(出願日)

(現況)

(特許済み、係属中、放棄済み)

(Status)

(patented, pending, abandoned)

(Application Serial No.)

(出願番号)

(Filing Date)

(出願日)

(現況)

(特許済み、係属中、放棄済み)

(Status)

(patented, pending, abandoned)

私は、ここに自己の知識にもとづいて行った陳述がすべて真実であり、自己の有する情報および信ずるところに従って行った陳述が真実であると信じ、さらに故意に虚偽の陳述等を行った場合、合衆国法典第18部第1001条により、罰金もしくは禁錮に処せられるか、またはこれらの刑が併科され、またかかる故意による虚偽の陳述が本願ないし本願に対して付与される特許の有効性を損うことがあることを認識して、以上の陳述を行ったことを宣言する。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Japanese Language Declaration

私は、合衆国法典第35部第119条にもとづく下記の外国特許出願または発明者証出願の外国優先権利益を主張し、さらに優先権の主張に係わる基礎出願の出願日前の出願日を有する外国特許出願または発明者証出願を以下に明記する：

Prior foreign applications
先の外国出願

Hei. 10-175340	Japan	9/6/98
(Number) (番号)	(Country) (国名)	(Day/Month/Year Filed) (出願の年月日)
Hei. 10-22036	Japan	29/1/99
(Number) (番号)	(Country) (国名)	(Day/Month/Year Filed) (出願の年月日)
Hei. 11-23300	Japan	29/1/99
(Number) (番号)	(Country) (国名)	(Day/Month/Year Filed) (出願の年月日)

Priority claimed
優先権の主張

<input checked="" type="checkbox"/> Yes あり	<input type="checkbox"/> No なし
<input checked="" type="checkbox"/> Yes あり	<input type="checkbox"/> No なし
<input checked="" type="checkbox"/> Yes あり	<input type="checkbox"/> No なし

私は、合衆国法典第35部第120条にもとづく下記の合衆国特許出願の利益を主張し、本願の請求の範囲各項に記載の主題が合衆国法典第35部第112条第1項に規定の態様で先の合衆国出願に開示されていない限度において、先の出願の出願日と本願の国内出願日またはPCT国際出願日の間に公表された連邦規則法典第37部第1章第56条項に記載の所要の情報を開示すべき義務を有することを認める：

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.) (出願番号)	(Filing Date) (出願日)
------------------------------------	------------------------

(現況) (特許済み、係属中、放棄済み)	(Status) (patented, pending, abandoned)
-------------------------	--

(Application Serial No.) (出願番号)	(Filing Date) (出願日)
------------------------------------	------------------------

(現況) (特許済み、係属中、放棄済み)	(Status) (patented, pending, abandoned)
-------------------------	--

私は、ここに自己の知識にもとづいて行った陳述がすべて真実であり、自己の有する情報および信ずるところに従って行った陳述が真実であると信じ、さらに故意に虚偽の陳述等を行った場合、合衆国法典第18部第1001条により、罰金もしくは禁錮に処せられるか、またはこれらの刑が併科され、またかかる故意による虚偽の陳述が本願ないし本願に対して付与される特許の有効性を損うことがあることを認識して、以上の陳述を行ったことを宣言する。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Japanese Language Declaration

委任状：私は、下記発明者として、以下の代理人をここに選任し、本願の手続を遂行すること並びにこれに関する一切の行為を特許商標庁に対して行うことを委任する。
(代理人氏名および登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Harold I. Kaplan,	Registration No. 16,958
Lawrence Rosenthal,	Registration No. 24,377
Steven B. Pokotilow,	Registration No. 26,405
Howard M. Gitten,	Registration No. 32,138
Matthew W. Siegal,	Registration No. 32,941

書類の送付先：

Send Correspondence to:

STROOCK & STROOCK & LAVAN LLP
180 Maiden Lane
New York, New York 10038-4982

直通電話連絡先：(名称および電話番号)

Direct Telephone Calls to: (name and telephone number)

STROOCK & STROOCK & LAVAN LLP
(212) 806-5400

唯一のまたは第一の発明者の氏名	Full name of sole or first inventor Minoru Usui
同発明者の署名	Inventor's signature
住所	Residence c/o Seiko Epson Corporation, 3-5, Owa 3-chome, Suwa-shi, Nagano, Japan
国籍	Citizenship Japan
郵便の宛先	Post Office Address c/o Seiko Epson Corporation
	3-5, Owa 3-chome, Suwa-shi, Nagano, Japan
第2の共同発明者の氏名 (該当する場合)	Full name of second joint inventor, if any Satoshi Shinada
同第2発明者の署名	Second Inventor's signature
住所	Residence c/o Seiko Epson Corporation, 3-5, Owa 3-chome, Suwa-shi, Nagano, Japan
国籍	Citizenship Japan
郵便の宛先	Post Office Address c/o Seiko Epson Corporation
	3-5, Owa 3-chome, Suwa-shi, Nagano, Japan

(第6またはそれ以降の共同発明者に対しても同様な情報および署名を提供すること。)

(Supply similar information and signature for third and subsequent joint inventors.)

Japanese Language Declaration

委任状：私は、下記発明者として、以下の代理人をここに選任し、本願の手續を遂行すること並びにこれに関する一切の行為を特許商標庁に対して行うことを委任する。
(代理人氏名および登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Harold I. Kaplan,	Registration No. 16,958
Lawrence Rosenthal,	Registration No. 24,377
Steven B. Pokotilow,	Registration No. 26,405
Howard M. Gitten,	Registration No. 32,138
Matthew W. Siegal,	Registration No. 32,941

書類の送付先：

Send Correspondence to:

STROOCK & STROOCK & LAVAN LLP
180 Maiden Lane
New York, New York 10038-4982

直通電話連絡先：(名称および電話番号)

Direct Telephone Calls to: (name and telephone number)

STROOCK & STROOCK & LAVAN LLP
(212) 806-5400

唯一のまたは第一の発明者の氏名		Takahiro Naka	
同発明者の署名	日付	Inventor's signature	Date
住所	Residence c/o Seiko Epson Corporation, 3-5, Owa 3-chome, Suwa-shi, Nagano, Japan		
国籍	Citizenship Japan		
郵便の宛先	Post Office Address c/o Seiko Epson Corporation		
		3-5, Owa 3-chome, Suwa-shi, Nagano, Japan	
第2の共同発明者の氏名 (該当する場合)		Hisashi Miyazawa	
同第2発明者の署名	日付	Inventor's signature	Date
住所	Residence c/o Seiko Epson Corporation, 3-5, Owa 3-chome, Suwa-shi, Nagano, Japan		
国籍	Citizenship Japan		
郵便の宛先	Post Office Address c/o Seiko Epson Corporation		
		3-5, Owa 3-chome, Suwa-shi, Nagano, Japan	

(第六またはそれ以降の共同発明者に対しても同様な情報および署名を提供すること。)

(Supply similar information and signature for third and subsequent joint inventors.)

Japanese Language Declaration

委任状：私は、下記発明者として、以下の代理人をここに選任し、本願の手続を遂行すること並びにこれに関する一切の行為を特許商標庁に対して行うことを委任する。
(代理人氏名および登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Harold I. Kaplan,	Registration No. 16,958
Lawrence Rosenthal,	Registration No. 24,377
Steven B. Pokotilow,	Registration No. 26,405
Howard M. Gitten,	Registration No. 32,138
Matthew W. Siegal,	Registration No. 32,941

書類の送付先：

Send Correspondence to:

STROOCK & STROOCK & LAVAN LLP
180 Maiden Lane
New York, New York 10038-4982

直通電話連絡先：(名称および電話番号)

Direct Telephone Calls to: (name and telephone number)

STROOCK & STROOCK & LAVAN LLP
(212) 806-5400

唯一のまたは第一の発明者の氏名

Takeo Seino

同発明者の署名

日付

Inventor's signature

Date

住所

Residence c/o Seiko Epson Corporation, 3-5, Owa
3-chome, Suwa-shi, Nagano, Japan

国籍

Citizenship Japan

郵便の宛先

Post Office Address

c/o Seiko Epson Corporation

3-5, Owa 3-chome, Suwa-shi, Nagano, Japan

第2の共同発明者の氏名 (該当する場合)

Hisashi Koike

同第2発明者の署名

日付

Inventor's signature

Date

住所

Residence c/o Seiko Epson Corporation, 3-5, Owa
3-chome, Suwa-shi, Nagano, Japan

国籍

Citizenship Japan

郵便の宛先

Post Office Address

c/o Seiko Epson Corporation

3-5, Owa 3-chome, Suwa-shi, Nagano, Japan

(第6またはそれ以降の共同発明者に対しても同様な情報および署名を提供すること。)

(Supply similar information and signature for third and subsequent joint inventors.)

Japanese Language Declaration

委任状：私は、下記発明者として、以下の代理人をここに選任し、本願の手続を遂行すること並びにこれに関する一切の行為を特許商標庁に対して行うことを委任する。
(代理人氏名および登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Harold I. Kaplan,	Registration No. 16,958
Lawrence Rosenthal,	Registration No. 24,377
Steven B. Pokotilow,	Registration No. 26,405
Howard M. Gitten,	Registration No. 32,138
Matthew W. Siegal,	Registration No. 32,941

書類の送付先：

Send Correspondence to:

STROOCK & STROOCK & LAVAN LLP
180 Maiden Lane
New York, New York 10038-4982

直通電話連絡先：(名称および電話番号)

Direct Telephone Calls to: (name and telephone number)

STROOCK & STROOCK & LAVAN LLP
(212) 806-5400

唯一のまたは第一の発明者の氏名		Takao Kobayashi	
同発明者の署名	日付	Inventor's signature	Date
住所	Residence c/o Seiko Epson Corporation, 3-5, Owa 3-chome, Suwa-shi, Nagano, Japan		
国籍	Citizenship Japan		
郵便の宛先	Post Office Address		
	c/o Seiko Epson Corporation		
	3-5, Owa 3-chome, Suwa-shi, Nagano, Japan		
第2の共同発明者の氏名 (該当する場合)		Masahiro Kanai	
同第2発明者の署名	日付	Inventor's signature	Date
住所	Residence c/o Seiko Epson Corporation, 3-5, Owa 3-chome, Suwa-shi, Nagano, Japan		
国籍	Citizenship Japan		
郵便の宛先	Post Office Address		
	c/o Seiko Epson Corporation		
	3-5, Owa 3-chome, Suwa-shi, Nagano, Japan		

(第六またはそれ以降の共同発明者に対しても同様な情報および署名を提供すること。)

(Supply similar information and signature for third and subsequent joint inventors.)

Japanese Language Declaration

委任状：私は、下記発明者として、以下の代理人をここに選任し、本願の手續を遂行すること並びにこれに関する一切の行為を特許商標庁に対して行うことを委任する。
(代理人氏名および登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Harold I. Kaplan,	Registration No. 16,958
Lawrence Rosenthal,	Registration No. 24,377
Steven B. Pokotilow,	Registration No. 26,405
Howard M. Gitten,	Registration No. 32,138
Matthew W. Siegal,	Registration No. 32,941

書類の送付先：

Send Correspondence to:

STROOCK & STROOCK & LAVAN LLP
180 Maiden Lane
New York, New York 10038-4982

直通電話連絡先：(名称および電話番号)

Direct Telephone Calls to: (name and telephone number)

STROOCK & STROOCK & LAVAN LLP
(212) 806-5400

唯一のまたは第一の発明者の氏名

Yasuko Hirano

同発明者の署名

日付

Inventor's signature

Date

住所

Residence c/o Seiko Epson Corporation, 3-5, Owa
3-chome, Suwa-shi, Nagano, Japan

国籍

Citizenship Japan

郵便の宛先

Post Office Address

c/o Seiko Epson Corporation

3-5, Owa 3-chome, Suwa-shi, Nagano, Japan

第2の共同発明者の氏名 (該当する場合)

Yasushi Akatsuka

同第2発明者の署名

日付

Inventor's signature

Date

住所

Residence c/o Seiko Epson Corporation, 3-5, Owa
3-chome, Suwa-shi, Nagano, Japan

国籍

Citizenship Japan

郵便の宛先

Post Office Address

c/o Seiko Epson Corporation

3-5, Owa 3-chome, Suwa-shi, Nagano, Japan

(第六またはそれ以降の共同発明者に対しても同様な情報および署名を提供すること。)

(Supply similar information and signature for third and subsequent joint inventors.)

Japanese Language Declaration

委任状：私は、下記発明者として、以下の代理人をここに選任し、本願の手續を遂行すること並びにこれに関する一切の行為を特許商標庁に対して行うことを委任する。
(代理人氏名および登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Harold I. Kaplan,	Registration No. 16,958
Lawrence Rosenthal,	Registration No. 24,377
Steven B. Pokotilow,	Registration No. 26,405
Howard M. Gitten,	Registration No. 32,138
Matthew W. Siegal,	Registration No. 32,941

書類の送付先：

Send Correspondence to:

STROOCK & STROOCK & LAVAN LLP
180 Maiden Lane
New York, New York 10038-4982

直通電話連絡先：(名称および電話番号)

Direct Telephone Calls to: (name and telephone number)

STROOCK & STROOCK & LAVAN LLP
(212) 806-5400

唯一のまたは第一の発明者の氏名		Takayuki Iijima	
同発明者の署名	日付	Inventor's signature	Date
住所		Residence c/o Seiko Epson Corporation, 3-5, Owa 3-chome, Suwa-shi, Nagano, Japan	
国籍		Citizenship Japan	
郵便の宛先		Post Office Address c/o Seiko Epson Corporation	
		3-5, Owa 3-chome, Suwa-shi, Nagano, Japan	
第2の共同発明者の氏名 (該当する場合)		Noriaki Okazawa	
同第2発明者の署名	日付	Inventor's signature	Date
住所		Residence c/o Seiko Epson Corporation, 3-5, Owa 3-chome, Suwa-shi, Nagano, Japan	
国籍		Citizenship Japan	
郵便の宛先		Post Office Address c/o Seiko Epson Corporation	
		3-5, Owa 3-chome, Suwa-shi, Nagano, Japan	

(第六またはそれ以降の共同発明者に対しても同様な情報および署名を提供すること。)

(Supply similar information and signature for third and subsequent joint inventors.)

Japanese Language Declaration

委任状：私は、下記発明者として、以下の代理人をここに選任し、本願の手續を遂行すること並びにこれに関する一切の行為を特許商標庁に対して行うことを委任する。
(代理人氏名および登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Harold I. Kaplan,	Registration No. 16,958
Lawrence Rosenthal,	Registration No. 24,377
Steven B. Pokotilow,	Registration No. 26,405
Howard M. Gitten,	Registration No. 32,138
Matthew W. Siegal,	Registration No. 32,941

書類の送付先：

Send Correspondence to:

STROOCK & STROOCK & LAVAN LLP
180 Maiden Lane
New York, New York 10038-4982

直通電話連絡先：(名称および電話番号)

Direct Telephone Calls to: (name and telephone number)

STROOCK & STROOCK & LAVAN LLP
(212) 806-5400

唯一のまたは第一の発明者の氏名

Hitoshi Matsumoto

同発明者の署名

日付

Inventor's signature

Date

住所

Residence c/o Seiko Epson Corporation, 3-5, Owa
3-chome, Suwa-shi, Nagano, Japan

国籍

Citizenship
Japan

郵便の宛先

Post Office Address

c/o Seiko Epson Corporation

3-5, Owa 3-chome, Suwa-shi, Nagano, Japan

第2の共同発明者の氏名(該当する場合)

Yasuhiro Ogura

同第2発明者の署名

日付

Inventor's signature

Date

住所

Residence c/o Seiko Epson Corporation, 3-5, Owa
3-chome, Suwa-shi, Nagano, Japan

国籍

Citizenship
Japan

郵便の宛先

Post Office Address

c/o Seiko Epson Corporation

3-5, Owa 3-chome, Suwa-shi, Nagano, Japan

(第六またはそれ以降の共同発明者に対しても同様な情報および署名を提供すること。)

(Supply similar information and signature for third and subsequent joint inventors.)